13 Wall & Ceiling LED>The Dark Light Ceiling Lights

12124H/B/W



24W Surface ceiling Dark light, IP20.

Complete with 700mA driver.


Complies with standard EN60598-1 and any other specific standards.

IP20 90 CRI DARK LIGHT CE

Downloads

IES

Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	The Dark Light Ceiling Lights
Order Code	12124H/B/W
Colour	Black
Material	Aluminium
Shape	Rectangular
Length	273mm
Width	37mm
Height	83mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	24W
IP Rating	IP20
Light Source	LED built in
Dimmable	No

Fitting

Input Type	Constant Current
Input Current	700mA
Voltage	32V
Safety Class	
Power(Watts)	22,4W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 3535
LED Brand	Bridgelux
LED Number	10
F Mark	

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes

Power(Watts)	16,8-29,4W
Power Factor	0,95
Constant Current	Yes
700mA	24-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20°C…+45°C
Operating Temp	85°C
Brand	Eaglerise
Protection	Over Load Protection, Over Voltage Protection, Short circuit Protection

Illumination Data

Colour Temperature	3000K
Lumen Output	1700lm
Light Efficiency	70,83lm/W
CRI	90
Beam Angle	38°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Weight	0.880kg
Pcs/Carton	30
Barcode	5291889074786
HS Code	9405413990

Certification & Warranty

Warranty	5 years