
12 Wall & Ceiling LED>The UGR19 Cylinders CCT V

12130D/W/V



CCT Variable 30W LED surface mounted downlight. IP44.

Complete with non-dimmable driver.


Complies with standard EN60598-1 and any other specific standards.

IP44 CCT V 90 CRI UGR19


Downloads

IES

Dimensions



Gallery



Physical Specification

Item Group	12 Wall & Ceiling LED
Family	The UGR19 Cylinders CCT V
Order Code	12130D/W/V
Colour	White
Material	Aluminium
Shape	Circular
Height	85mm

Diameter	200mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⏚
Power(Watts)	30W
IP Rating	IP44
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
IP Rating	IP44
Light Source	LED built in
LED Type	SMD
F Mark	F

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes

Output	750mA
IP Rating	IP20
Dimmable	No

Illumination Data

Colour Temperature	3000K-4000K-5000K
Lumen Output	3000lm
Light Efficiency	100lm/W
CRI	90
Beam Angle	90°
Illumination Diagram	
UGR	19

Packing Info

Box Weight	1.120kg
Pcs/Carton	12
Barcode	5291889082828
HS Code	9405413990

Certification & Warranty

Warranty	5 years