
11 Office & Kitchen>Recessed LED Linear Profiles

38152RL/W/C



10W ceiling to wall corner for 38152R.


Complete with 200mA driver , 4pcs fixing clips, 4pcs connectors & 2pcs end cups.

Complies with standard EN60598-1 and any other specific standards.

IP20 90 CRI CE

Downloads

Dimensions



Gallery



Physical Specification

Item Group	11 Office & Kitchen
Family	Recessed LED Linear Profiles
Order Code	38152RL/W/C
Colour	White
Material	Aluminium
Diffuser Material	Plastic
Shape	Rectangular

Length	134x134mm
Width	70mm
Height	60mm
Cutout Hole Width	100x100mm
Cutout Hole Length	60mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	200mA
Voltage	42V
Power(Watts)	8,4W
IP Rating	IP20
Light Source	LED built in

LED Type	SMD 2835
LED Brand	Epistar
LED Number	72

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	6-8,4W
Power Factor	0,9
Constant Current	Yes
200mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Metal
Output Terminal	Connector
Brand	ATG

Illumination Data

Colour Temperature	4000K
Lumen Output	900m
Light Efficiency	90lm/W
CRI	90
Illumination Diagram	

Packing Info

Box Weight	0.650kg
Pcs/Carton	6

Barcode	5291889062684
HS Code	9405409900

Certification & Warranty

Warranty	3 Years
Weee Directive	Yes