
04 Recessed Spots Adjustable LED>The COB Recessed Cylinders

51211C/B/W



2x11W COB LED recessed adjustable spot, for general lighting applications.

Supplied with Black & Brass reflectors.

Complete with 250mA drivers.

Complies with standard EN60598-1 and any other specific standards.

IP20 90 CRI ADJUSTABLE DARK LIGHT CE

Downloads

IES

Dimensions



Gallery



Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	The COB Recessed Cylinders
Order Code	51211C/B/W
Colour	Black
Material	Die Cast
Shape	Rectangular
Length	171mm

Width	90mm
Height	98mm
Cutout Hole Width	85mm
Cutout Hole Length	165mm
Recessed Ceiling	Yes
Depth Required	110mm
Indoor	Yes
Adjustable	2 Directions

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	2x11W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	250mA
Voltage	37V
Safety Class	
Power(Watts)	2x9,25W
IP Rating	IP20
Light Source	LED built in

LED Type	COB
LED Brand	Luminus
LED Number	2
F Mark	

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	7,5-10W
Power Factor	0,8
Constant Current	Yes
250mA	30-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	KEGU

Illumination Data

Colour Temperature	3000K
Lumen Output	2x820lm
Light Efficiency	74,5lm/W
CRI	90
Beam Angle	38°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Weight	0.720kg
Pcs/Carton	20
Barcode	5291889059547
HS Code	9405413990

Certification & Warranty

Warranty	5 years