21 Industrial & Floodlights>The Industrial IP65 UFO Range DALI

# 63150NL/C



150W SMD LED DALI Industrial High Bay, IP65.

Supplied with DALI 2 driver.


Complies with standard EN60598-1 and any other specific standards.

IP65 DALI 80 CRI DALI DIMMABLE 90° CE

## Downloads

IES

## Dimensions




## Physical Specification

| | |
|---|---|
| Item Group | 21 Industrial & Floodlights |
| Family | The Industrial IP65 UFO Range DALI |
| Order Code | 63150NL/C |
| Colour | Black |
| Material | Aluminium |
| Diffuser Material | PC |
| Shape | Circular |
| Height | 169mm |
| Diameter | 310mm |
| Suspended Ceiling | Yes |
| Indoor | Yes |
| Outdoor | Yes |

| | |
|---|---|
| Adjustable | No |

## Electrical Characteristics

| | |
|---|---|
| Gear | Built In |

### Fitting + Driver

| | |
|---|---|
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class |  |
| Power(Watts) | 150W |
| IP Rating | IP65 |
| Light Source | LED built in |
| Dimmable | Yes |
| Dimmer type | Dali |
| Cable Length | 150cm |
| F Mark |  |

### Fitting

| | |
|---|---|
| Input Type | Constant Current |
| Light Source | LED built in |
| LED Type | SMD 2835 |

### Gear

| | |
|---|---|
| Gear Type | Led Driver |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power Factor | 0,9 |
| Constant Current | Yes |
| Safety Class |  |

| | |
|---|---|
| Brand | Lifud |

## Illumination Data

| | |
|---|---|
| Colour Temperature | 4000K |
| Lumen Output | 22500lm |
| Light Efficiency | 150lm/W |
| CRI | 80 |
| Beam Angle | 90° |
| Illumination Diagram |  |



## Packing Info

| | |
|---|---|
| Box Weight | 3.000kg |
| Pcs/Carton | 1 |
| Barcode | 5291889078371 |
| HS Code | 9405413990 |

## Certification & Warranty

| | |
|---|---|
| Warranty | 5 years |
| Weee Directive | Yes |