21 Emergency Lights>Emergency LED Plafo

67280ANE/G/W



15W Emergency LED plafo light, IP65, ideal for both indoor and outdoor installation.

Complete with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.

IP65 IK08 80 CRI CE

Downloads

IES CE

Dimensions



Accessories



050410/AN

Physical Specification

Item Group	21 Emergency Lights
Family	Emergency LED Plafo
Order Code	67280ANE/G/W
Colour	Grey
Material	Plastic
Diffuser Material	PC

Shape	Circular
Height	78mm
Diameter	300mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No
IK Rating	8

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⧈
Power(Watts)	15W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	300mA
Power(Watts)	15W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar

F Mark	

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	7,5-15W
Power Factor	0,9
Constant Current	Yes
300mA	25-50V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector

Illumination Data

Colour Temperature	3000K
Lumen Output	1000lm
Light Efficiency	66lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	1.420kg
Pcs/Carton	10
Barcode	5291889051725
HS Code	9405114090

Certification & Warranty

Warranty	2 years