13 Plafo>The LED Plafo Outdoor

67280AN/W/W



24W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.

IP65 IK08 80 CRI CE

Downloads

IES CE

Dimensions



Physical Specification

Item Group	13 Plafo
Family	The LED Plafo Outdoor
Order Code	67280AN/W/W
Colour	White
Material	Plastic
Diffuser Material	PC
Shape	Circular
Height	83mm
Diameter	300mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Adjustable	No
IK Rating	8

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	24W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	600mA
Voltage	38V
Power(Watts)	22,8W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	121
F Mark	

Gear

Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	15,6-26W
Power Factor	0,9
Constant Current	Yes
600mA	26-43,5V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise

Illumination Data

Colour Temperature	3000K
Lumen Output	1440lm
Light Efficiency	60lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Length	30,5cm
Box Width	30,5cm
Box Height	8,5cm
Box Weight	1.230kg
Pcs/Carton	10
Barcode	5291889043300
HS Code	9405114090

Certification & Warranty

Warranty	2 years