13 Plafo>The LED Plafo Outdoor

67280N/W/W



16W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.

IP65 IK08 80 CRI CE

Downloads

IES CE

Dimensions



Physical Specification

Item Group	13 Plafo
Family	The LED Plafo Outdoor
Order Code	67280N/W/W
Colour	White
Material	Plastic
Diffuser Material	PC
Shape	Circular
Height	75mm
Diameter	260mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Adjustable	No
IK Rating	8

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	16W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	500mA
Voltage	30V
Power(Watts)	15W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
LED Number	81
F Mark	

Gear

Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	8,5-16W
Power Factor	0,9
Constant Current	Yes
500mA	19-32V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise

Illumination Data

Colour Temperature	3000K
Lumen Output	960lm
Light Efficiency	60lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Length	27cm
Box Width	27cm
Box Height	8cm
Box Weight	0.980kg
Pcs/Carton	10
Barcode	5291889043263
HS Code	9405114090

Certification & Warranty

Warranty	2 years