13 Wall & Ceiling LED>Outdoor Slim Range Up & down beam

67412/AN/W



2x6W LED wall light with adjustable beam, ideal for both indoor and outdoor installation.


Complete with 500mA driver.

Complies with standard EN60598-1 and any other specific standards.

IP54 80 CRI CE

Downloads

Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	Outdoor Slim Range Up & down beam
Order Code	67412/AN/W
Colour	Anthracite
Material	Die Cast
Shape	Rectangular
Length	180mm
Width	42mm
Height	115mm
Surface Wall	Yes
Indoor	Yes
Outdoor	Yes

Adjustable	No

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	2x6W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	500mA
Voltage	10V
Safety Class	
Power(Watts)	5W
IP Rating	IP54
Light Source	LED built in
LED Type	COB
LED Brand	Edison
F Mark	

Gear

Gear Type	Led Driver
Input Voltage	220-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	6-12W
Power Factor	0,5
Constant Current	Yes
500mA	12-24V
IP Rating	IP20
Safety Class	
Brand	Eaglerise
Protection	0

Illumination Data

Colour Temperature	3000K
Lumen Output	2x400lm
Light Efficiency	66,67lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	0.933kg
Pcs/Carton	12
Barcode	5291889056362
HS Code	9405409900

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes