13 Wall & Ceiling LED>The Roof tile Range Die cast

67422A/AN/W



2x6W COB LED Outdoor Slim Range Up & down beam.


Complete with driver

Complies with standard EN60598-1 and any other specific standards.

IP54 80 CRI CE

Downloads

Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	The Roof tile Range Die cast
Order Code	67422A/AN/W
Colour	Anthracite
Material	Die Cast
Shape	Rectangular
Length	190mm
Width	120mm
Height	50mm
Surface Wall	Yes
Indoor	Yes
Outdoor	Yes

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	2x6W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	500mA
Voltage	20V
Power(Watts)	10W
IP Rating	IP54
Light Source	LED built in
LED Type	COB
LED Brand	Edison

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	6-12W
Power Factor	0,5

Constant Current	Yes
500mA	12-24V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50ºC
Operating Temp	75ºC
Housing Material	Plastic
Output Terminal	Cable
Brand	Eaglerise

Illumination Data

Colour Temperature	3000K
Lumen Output	2x400lm
Light Efficiency	66,67lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Length	13cm
Box Width	5,5cm
Box Height	21cm
Box Weight	0.750kg
Pcs/Carton	12
Barcode	5291889053026
HS Code	9405409900

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes