13 Wall & Ceiling LED>Wall Adjustable Beams

# 67440A/AN/W



11W LED Outdoor Wall with adjustable beam, IP54.


Complete with driver.

Complies with standard EN60598-1 and any other specific standards.

IP54 80 CRI CE

## Downloads

## Dimensions




## Gallery



## Physical Specification

| | |
|---|---|
| Item Group | 13 Wall & Ceiling LED |
| Family | Wall Adjustable Beams |
| Order Code | 67440A/AN/W |
| Colour | Anthracite |
| Material | Die Cast |
| Diffuser Material | Glass |
| Shape | Rectangular |

| | |
|---|---|
| Length | 140mm |
| Width | 125mm |
| Height | 145mm |
| Surface Wall | Yes |
| Indoor | Yes |
| Outdoor | Yes |

## Electrical Characteristics

| | |
|---|---|
| Gear | Built In |

### Fitting + Driver

| | |
|---|---|
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class |  |
| Power(Watts) | 11W |
| IP Rating | IP54 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark |  |

### Fitting

| | |
|---|---|
| Input Type | Constant Current |
| Input Current | 350mA |
| Voltage | 26V |
| Safety Class |  |
| Power(Watts) | 9,1W |
| IP Rating | IP54 |
| Light Source | LED built in |
| LED Type | SMD 2835 |

| | |
|---|---|
| LED Brand | Edison |

### Gear

| | |
|---|---|
| Gear Type | Led Driver |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 5,3-9W |
| Power Factor | 0,5 |
| Constant Current | Yes |
| 350mA | 15-26V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Brand | Eaglerise |

## Illumination Data

| | |
|---|---|
| Colour Temperature | 3000K |
| Lumen Output | 700lm |
| Light Efficiency | 63,64lm/W |
| CRI | 80 |
| Illumination Diagram |  |

## Packing Info

| | |
|---|---|
| Box Length | 15,5cm |
| Box Width | 15,5cm |
| Box Height | 14cm |
| Box Weight | 1.562kg |
| Pcs/Carton | 8 |
| Barcode | 5291889058182 |

| | |
|---|---|
| HS Code | 9405409900 |

## Certification & Warranty

| | |
|---|---|
| Warranty | 2 Years |
| Weee Directive | Yes |