19 Garden & Underwater>Corridor Bollards

67494A/AN/W



3W Bollard with 2x1000W Schuko Sockets , IP44.

Complete with 350mA driver


Complies with standard EN60598-1 and any other specific standards.

IP44 IK05 80 CRI CE

Downloads

IES

Dimensions



Physical Specification

Item Group	19 Garden & Underwater
Family	Corridor Bollards
Order Code	67494A/AN/W
Colour	Anthracite
Material	Die Cast
Shape	Circular
Height	490mm
Diameter	100mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No
IK Rating	5

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	3W
IP Rating	IP44
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	350mA
Voltage	8V
Power(Watts)	2,8W
IP Rating	IP44
Light Source	LED built in
LED Type	SMD 3014
LED Brand	Philips

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	2,1-4,2W
Power Factor	0,9

Constant Current	Yes
350mA	6-12V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	KGP

Illumination Data

Colour Temperature	3000K
Lumen Output	240lm
Light Efficiency	80lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	2.075kg
Pcs/Carton	4
Barcode	5291889067092
HS Code	9405413990

Certification & Warranty

Warranty	2 years