18 Wall Recessed & Inground>The Inground Mini Series

69042M/AL/W



2W LED inground, IP67, aluminium, for path illumination.

Requires 700mA driver.


Complies with standard EN60598-1 and any other specific standards.

IP67 IK08 WALK OVER 90 CRI DIMMABLE CE

Downloads

IES


Dimensions




Gallery



Must be ordered separately



89004A



89004AT

Physical Specification

Item Group	18 Wall Recessed & Inground
Family	The Inground Mini Series
Order Code	69042M/AL/W
Colour	Aluminium
Material	Aluminium
Shape	Circular
Height	44mm
Diameter	27mm
Cutout Hole Diameter	22mm decking 26mm concrete
Inground	Yes
Depth Required	60mm deck 95mm+300mm drainage Concrete
Indoor	Yes
Outdoor	Yes
Adjustable	No
IK Rating	8

Electrical Characteristics

Fitting

Input Type	Constant Current
Input Current	700mA
Voltage	3,1V
Safety Class	III
Power(Watts)	2W
IP Rating	IP67
Light Source	LED built in
LED Brand	Osram
LED Number	1
Cable Length	200cm

F Mark	F

Illumination Data

Colour Temperature	3000K
Lumen Output	150lm
Light Efficiency	75lm/W
CRI	90
Beam Angle	24°
Illumination Diagram	

Packing Info

Box Weight	0.160kg
Pcs/Carton	50
Barcode	5291889061502
HS Code	9405413990

Certification & Warranty

Warranty	2 years