# 18 Wall Recessed & Inground>The Inground Tiltable Range

# 69072/W



3W COB LED inground uplight with a 5° beam which is tiltable +/- 20°. IP67, stainless steel 316L and die cast aluminium body.

Supplied with non-dimmable LED driver and box for concrete installation.


Complies with standard EN60598-1 and any other specific standards.




## Downloads





## Dimensions




## Gallery





## Physical Specification

| | |
|---|---|
| Item Group | 18 Wall Recessed & Inground |
| Family | The Inground Tiltable Range |
| Order Code | 69072/W |
| Colour | Stainless Steel |
| Material | Die Cast |
| Shape | Circular |
| Height | 115mm |

| | |
|---|---|
| Diameter | 100mm |
| Cutout Hole Diameter | 90mm |
| Inground | Yes |
| Depth Required | 135mm+300mm drainage |
| Indoor | Yes |
| Outdoor | Yes |
| Adjustable | 1 Direction |
| IK Rating | 10 |

## Electrical Characteristics

| | |
|---|---|
| Gear | Built In |

### Fitting + Driver

| | |
|---|---|
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class |  |
| Power(Watts) | 3W |
| IP Rating | IP67 |
| Light Source | LED built in |
| Dimmable | No |
| Cable Length | 200cm |
| F Mark |  |

### Fitting

| | |
|---|---|
| Input Type | Constant Current |
| Light Source | LED built in |
| LED Type | COB |
| LED Brand | Cree |

### Gear

| | |
|---|---|
| Gear Type | Led Driver |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power Factor | 0,4 |
| Constant Current | Yes |
| Dimmable | No |
| Housing Material | Plastic |
| Output Terminal | Connector |

## Illumination Data

| | |
|---|---|
| Colour Temperature | 3000K |
| Lumen Output | 210lm |
| Light Efficiency | 70lm/W |
| CRI | 80 |
| Beam Angle | 5° |
| Illumination Diagram |  |

## Packing Info

| | |
|---|---|
| Box Weight | 1.120kg |
| Pcs/Carton | 18 |
| Barcode | 5291889079620 |
| HS Code | 9405413990 |

## Certification & Warranty

| | |
|---|---|
| Warranty | 2 years |
| Weee Directive | Yes |