18 Wall Recessed & Inground>The Inground Tiltable Range

69074B/W



9x1,5W COB LED inground uplight with a 36° beam which is tiltable +/-20°. IP67, stainless steel 316L and die cast aluminium body.

Supplied with non-dimmable LED driver and box for concrete installation.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery





Physical Specification

Item Group	18 Wall Recessed & Inground
Family	The Inground Tiltable Range
Order Code	69074B/W
Colour	Stainless Steel
Material	Die Cast
Shape	Circular
Height	190mm

Diameter	180mm
Cutout Hole Diameter	170mm
Inground	Yes
Depth Required	210mm+300mm drainage
Indoor	Yes
Outdoor	Yes
Adjustable	1 Direction
IK Rating	10

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	9x1,5W
IP Rating	IP67
Light Source	LED built in
Dimmable	No
Cable Length	200cm
F Mark	

Fitting

Input Type	Constant Current
Light Source	LED built in
LED Type	COB
LED Brand	Cree

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power Factor	0,9
Constant Current	Yes
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector

Illumination Data

Colour Temperature	3000K
Lumen Output	1000lm
Light Efficiency	74,07lm/W
CRI	80
Beam Angle	36°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Weight	3.650kg
Pcs/Carton	4
Barcode	5291889079644
HS Code	9405413990

Certification & Warranty

Warranty	2 years
Weee Directive	Yes