
07 Strips & Profiles>230V Neon Flex Lightline 7864/W



230V Waterproof Square Neonflex 9W/m, IP65 .

Supplied in 50m rolls.

Can be cut every 1m.

Complete power supply 7864P.

Avoid direct sunlight.

Complies with standard EN60598-1 and any other specific standards.



Downloads




Dimensions



Accessories


7864C


7864E


7864F


7864P

Physical Specification

Item Group	07 Strips & Profiles
Family	230V Neon Flex Lightline
Order Code	7864/W
Material	PVC

Shape	Rectangular
Length	50000mm
Width	8mm
Height	12mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⧈
Power(Watts)	9W/m
IP Rating	IP65
Light Source	LED built in
Dimmable	Yes
Dimmer type	Triac
F Mark	Ⓕ

Fitting

IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar

LED Number	120LEDs/m

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	450W
Power Factor	0,9
IP Rating	IP65


Illumination Data

Colour Temperature	3000K
Lumen Output	270lm
Light Efficiency	30lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	0.154kg
Pcs/Carton	50
Barcode	5291889066507
HS Code	9405423100

Energy Label



Energy Class	F

Certification & Warranty

Warranty	2 years