
05 Downlights Fixed>The IP54 & IP65 Downlights CCT V

10110BX/W/V



10W CCT Variable SMD recessed downlight.

Complete with non-dimmable driver.


Complies with standard EN60598-1 and any other specific standards.

IP54 CCT V 90 CRI CE

Downloads

IES

Dimensions



Physical Specification

Item Group	05 Downlights Fixed
Family	The IP54 & IP65 Downlights CCT V
Order Code	10110BX/W/V
Colour	White
Material	Aluminium
Shape	Circular
Height	50mm
Diameter	86mm
Cutout Hole Diameter	75mm
Recessed Ceiling	Yes
Depth Required	60mm
Indoor	Yes

Outdoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10W
IP Rating	IP54
Light Source	LED built in
F Mark	

Fitting

Input Type	Constant Current
Input Current	250mA
Light Source	LED built in
LED Type	SMD

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Output	250mA

Illumination Data

Colour Temperature	3000K-4000K-5000K
Lumen Output	900lm
Light Efficiency	90lm/W
CRI	90
Beam Angle	90
Illumination Diagram	

Packing Info

Box Weight	0.250kg
Pcs/Carton	50
Barcode	5291889092674
HS Code	9405413990

Certification & Warranty

Warranty	5 years