05 Downlights Fixed>Floating Round Panels Range Adjustable Cut Out Hole 10110CE/W



10W Downlight LED, IP20

Complete with 250mA driver.


Complies with standard EN60598-1 and any other specific standards.

IP20 90 CRI CE

Downloads

IES

Dimensions



Gallery



Physical Specification

Item Group	05 Downlights Fixed
Family	Floating Round Panels Range Adjustable Cut Out Hole
Order Code	10110CE/W
Material	Aluminium
Diffuser Material	PC
Shape	Circular
Height	10mm

Diameter	120mm
Cutout Hole Diameter	60mm-100mm
Recessed Ceiling	Yes
Depth Required	40mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	250mA
Voltage	38V
Safety Class	
Power(Watts)	9,5W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 4014

LED Brand	Zhaochi

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	7,5-10,5W
Power Factor	0,5
Constant Current	Yes
250mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Eaglerise


Illumination Data

Colour Temperature	3000K
Lumen Output	1150lm
Light Efficiency	115lm/W
CRI	90
Illumination Diagram	

Packing Info

Box Weight	0.202kg
Pcs/Carton	40
Barcode	5291889066422
HS Code	9405413990

Energy Label



Energy Class	D
Energy Consumption	10kWh/1000h

Certification & Warranty

Warranty	2 years