05 Downlights Fixed>The 3-12W Round Recessed Panels Aluminium 10112FA/B/C



12W slim downlight LED, IP40, ideal for commercial applications such as offices, galleries and showrooms.

Complete with 250mA non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.

IP40 80 CRI CE


Downloads

IES CE

Dimensions



Gallery



Physical Specification

Item Group	05 Downlights Fixed
Family	The 3-12W Round Recessed Panels Aluminium
Order Code	10112FA/B/C
Colour	Black
Material	Die Cast
Diffuser Material	Acrylic
Shape	Circular

Height	22mm
Diameter	173mm
Cutout Hole Diameter	155mm
Recessed Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⧈
Power(Watts)	12W
IP Rating	IP40
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	320mA
Voltage	42V
Safety Class	III
Power(Watts)	10,5W
IP Rating	IP40
Light Source	LED built in
LED Type	SMD 2835

LED Brand	Epistar
LED Number	60

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	6,75-10,5W
Power Factor	0,9
Constant Current	Yes
250mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50°C
Operating Temp	75°C
Housing Material	Plastic
Brand	Lifud

Illumination Data

Colour Temperature	4000K
Lumen Output	840lm
Light Efficiency	70lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	

Packing Info

Box Length	23,5cm

Box Width	3,1cm
Box Height	18cm
Box Weight	0.396kg
Pcs/Carton	30
Barcode	5291889052487
HS Code	9405119090

Certification & Warranty

Warranty	2 years
Weee Directive	Yes