06 Downlights Fixed LED>The Outdoor/Bathroom IP65 Range Die cast 10115G/W/W



15W LED recessed downlight, IP65. Suitable for Indoor/Outdoor installation..

Complete with 350mA driver.


Complies with standard EN60598-1 and any other specific standards.

IP65 80 CRI CE

Downloads

IES CE

Dimensions



Gallery




Physical Specification

Item Group	06 Downlights Fixed LED
Family	The Outdoor/Bathroom IP65 Range Die cast
Order Code	10115G/W/W
Colour	White
Material	Die Cast
Shape	Circular
Height	65mm

Diameter	110mm
Cutout Hole Diameter	100mm
Recessed Ceiling	Yes
Depth Required	95mm
Indoor	Yes
Outdoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
Cable Length	200cm
F Mark	

Fitting

Input Type	Constant Current
Input Current	350mA
Voltage	37V
Safety Class	
Power(Watts)	12,95W
IP Rating	IP65
Light Source	LED built in

LED Type	COB
LED Brand	Cree
F Mark	

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	10-14,7W
Power Factor	0,9
Constant Current	Yes
350mA	27-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Kegu

Illumination Data

Colour Temperature	3000K
Lumen Output	1125lm
Light Efficiency	75lm/W
CRI	80
Beam Angle	60°
Illumination Diagram	

Packing Info

Box Length	13,5cm

Box Width	13cm
Box Height	9cm
Box Weight	0,49kg
Pcs/Carton	20
Barcode	5291889051886
HS Code	9405409900

Certification & Warranty

Warranty	3 Years
Weee Directive	Yes