05 Downlights Fixed>The IP54 & IP65 Downlights CCT V

10125BX/W/V



25W CCT Variable SMD recessed downlight.

Complete with non-dimmable driver.


Complies with standard EN60598-1 and any other specific standards.

IP65 CCT V 90 CRI CE

Downloads

IES

Dimensions



Physical Specification

Item Group	05 Downlights Fixed
Family	The IP54 & IP65 Downlights CCT V
Order Code	10125BX/W/V
Colour	White
Material	Aluminium
Shape	Circular
Height	50mm
Diameter	190mm
Cutout Hole Diameter	170mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes

Outdoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	25W
IP Rating	IP65
Light Source	LED built in
F Mark	

Fitting

Input Type	Constant Current
Input Current	650mA
Light Source	LED built in
LED Type	SMD

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Output	650mA

Illumination Data

Colour Temperature	3000K-4000K-5000K
Lumen Output	2250lm
Light Efficiency	90lm/W
CRI	90
Beam Angle	90
Illumination Diagram	

Packing Info

Box Weight	0.860kg
Pcs/Carton	20
Barcode	5291889092704
HS Code	9405413990

Certification & Warranty

Warranty	5 years