05 Downlights Fixed>The IP54 Downlights CCT V

10125B/W/V



25W LED CCT Variable recessed downlight, IP54. Suitable for bathroom installations.

Complete with non-dimmable driver.


Complies with standard EN60598-1 and any other specific standards.

IP54 CCT V 80 CRI CE

Downloads

IES CE

Dimensions



Gallery





Physical Specification

Item Group	05 Downlights Fixed
Family	The IP54 Downlights CCT V
Order Code	10125B/W/V
Colour	White
Material	Die Cast
Diffuser Material	Plastic
Shape	Circular

Height	46mm
Diameter	228mm
Cutout Hole Diameter	210mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Outdoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⧈
Power(Watts)	25W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	650mA
Safety Class	III
IP Rating	IP54
Light Source	LED built in
LED Type	SMD 2835

F Mark	

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Constant Current	Yes
Output	650mA
IP Rating	IP20
Safety Class	
Dimmable	No
Brand	0

Illumination Data

Colour Temperature	3000K-4000K-5000K
Lumen Output	2000lm
Light Efficiency	80lm/W
CRI	80
Beam Angle	90°
Illumination Diagram	

Packing Info

Box Weight	1.230kg
Pcs/Carton	10
Barcode	5291889082378
HS Code	9405413990

Certification & Warranty

Warranty	2 years