04 Recessed Spots Adjustable LED>The COB Dark Light

11107FD/W/C



7W COB LED Adjustable Dark Light recessed spot IP20.

Complete with 300mA driver.

Complies with standard EN60598-1 and any other specific standards.

IP20 90 CRI ADJUSTABLE DARK LIGHT CE

Downloads

IES

Dimensions



Gallery



Physical Specification

Item Group	04 Recessed Spots Adjustable LED
Family	The COB Dark Light
Order Code	11107FD/W/C
Colour	White
Material	Die Cast
Shape	Circular
Height	83mm

Diameter	95mm
Cutout Hole Diameter	80mm
Recessed Ceiling	Yes
Depth Required	110mm
Indoor	Yes
Adjustable	1 Direction

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⧈
Power(Watts)	7W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	300mA
Voltage	21V
Safety Class	III
Power(Watts)	6,2W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Epistar

LED Number	1

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	4,2-7,2W
Power Factor	0,9
Constant Current	Yes
300mA	14-24V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	Lifud

Illumination Data

Colour Temperature	4000K
Lumen Output	560lm
Light Efficiency	80lm/W
CRI	90
Beam Angle	60°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Length	11,5cm
Box Width	10cm
Box Height	11,5cm

Box Weight	0.276kg
Pcs/Carton	50
Barcode	5291889052104
HS Code	9405413990

Certification & Warranty

Warranty	2 years