13 Wall & Ceiling LED>The Dark Light Mirror Cylinders

12112X/B/W



12W Ceiling spot, IP20.

Complete with 300mA driver.


Complies with standard EN60598-1 and any other specific standards.

IP20 90 CRI DARK LIGHT CE

Downloads

IES

Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	The Dark Light Mirror Cylinders
Order Code	12112X/B/W
Colour	Black
Material	Aluminium
Shape	Circular
Height	58mm
Diameter	100mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	12W
IP Rating	IP20
Light Source	LED built in
Dimmable	No

Fitting

Input Type	Constant Current
Input Current	300mA
Voltage	36V
Safety Class	
Power(Watts)	10,8W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 3030
LED Brand	Sanan
LED Number	9
F Mark	

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes

Power(Watts)	7,2-12,6W
Power Factor	0,85
Constant Current	Yes
300mA	24-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20°C…+60°C
Operating Temp	90°C
Brand	Eaglerise
Protection	Over Load Protection, Over Voltage Protection, Short circuit Protection

Illumination Data

Colour Temperature	3000K
Lumen Output	960lm
Light Efficiency	80lm/W
CRI	90
Beam Angle	38°
Illumination Diagram	
Dark Light	Yes

Packing Info

Box Weight	0.457kg
Pcs/Carton	40
Barcode	5291889074465
HS Code	9405413990

Certification & Warranty

Warranty	5 years