12 Wall & Ceiling LED>COB Ceiling Cylinders

# 12122C/B/W



22W COB LED Cylinder, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.

IP20 90 CRI CE

## Downloads

IES

## Dimensions




## Physical Specification

| | |
|---|---|
| Item Group | 12 Wall & Ceiling LED |
| Family | COB Ceiling Cylinders |
| Order Code | 12122C/B/W |
| Colour | Black |
| Material | Die Cast |
| Shape | Circular |
| Height | 100mm |
| Diameter | 100mm |
| Surface Ceiling | Yes |
| Indoor | Yes |
| Adjustable | No |

## Electrical Characteristics

| | |
|---|---|
| Gear | Built In |

### Fitting + Driver

| | |
|---|---|
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class |  |
| Power(Watts) | 22W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark |  |

### Fitting

| | |
|---|---|
| Input Type | Constant Current |
| Input Current | 500mA |
| Voltage | 39,4V |
| Power(Watts) | 19,7W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | COB |
| LED Brand | Bridgelux |

### Gear

| | |
|---|---|
| Gear Type | Led Driver |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 15-21W |
| Power Factor | 0,95 |

| | |
|---|---|
| Constant Current | Yes |
| 500mA | 30-42V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Housing Material | Plastic |
| Brand | Kegu |

## Illumination Data

| | |
|---|---|
| Colour Temperature | 3000K |
| Lumen Output | 1500lm |
| Light Efficiency | 68,18lm/W |
| CRI | 90 |
| Beam Angle | 38° |
| Illumination Diagram |  |

## Packing Info

| | |
|---|---|
| Box Length | 14,5cm |
| Box Width | 14cm |
| Box Height | 11cm |
| Box Weight | 0.580kg |
| Pcs/Carton | 20 |
| Barcode | 5291889059370 |
| HS Code | 9405413990 |

## Certification & Warranty

| | |
|---|---|
| Warranty | 5 years |