13 Wall & Ceiling LED>The Backlight Cylinders

12128A/W/W



26W Downlight + 2W Uplight COB LED Cylinder. Gun Black Reflector.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.

IP20 90 CRI DARK LIGHT 60°

Downloads

IES

Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	The Backlight Cylinders
Order Code	12128A/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	130mm
Diameter	115mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⏚
Power(Watts)	26W+2W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	700mA
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Cree

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	19,6-29,4W
Constant Current	Yes
700mA	28-42V
IP Rating	IP20

Safety Class	
Dimmable	No
Housing Material	Plastic

Illumination Data

Colour Temperature	3000K
Lumen Output	2600lm
Light Efficiency	92,86lm/W
CRI	90
Beam Angle	60°
Illumination Diagram	
Dark Light	Yes

Packing Info

Pcs/Carton	20
Barcode	5291889079590
HS Code	9405413990

Certification & Warranty

Warranty	3 years
Weee Directive	Yes