13 Wall & Ceiling LED>Adjustable Display Spots

# 12208LA/W/W



2x8W COB LED adjustable ceiling downlight, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.

IP20 80 CRI ADJUSTABLE CE

## Downloads

IES

## Dimensions




## Physical Specification

| | |
|---|---|
| Item Group | 13 Wall & Ceiling LED |
| Family | Adjustable Display Spots |
| Order Code | 12208LA/W/W |
| Colour | White |
| Material | Aluminium |
| Shape | Circular |
| Height | 40mm |
| Diameter | 2x78mm |
| Surface Ceiling | Yes |
| Surface Wall | Yes |
| Indoor | Yes |
| Adjustable | 2 Directions |

## Electrical Characteristics

| | |
|---|---|
| Gear | Built In |

### Fitting + Driver

| | |
|---|---|
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class |  |
| Power(Watts) | 2x8W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark |  |

### Fitting

| | |
|---|---|
| Input Type | Constant Current |
| Input Current | 700mA |
| Voltage | 9V |
| Power(Watts) | 2x6,3W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | COB |
| LED Brand | Bridgelux |
| LED Number | 2 |

### Gear

| | |
|---|---|
| Gear Type | Led Driver |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 3,5-6,3W |

| | |
|---|---|
| Power Factor | 0,5 |
| Constant Current | Yes |
| 700mA | 5-9V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Housing Material | Plastic |
| Brand | KEGU |

## Illumination Data

| | |
|---|---|
| Colour Temperature | 3000K |
| Lumen Output | 2x600lm |
| Light Efficiency | 75lm/W |
| CRI | 80 |
| Beam Angle | 25° |
| Illumination Diagram |  |

## Packing Info

| | |
|---|---|
| Box Length | 18,5cm |
| Box Width | 11,5cm |
| Box Height | 20cm |
| Box Weight | 0.988kg |
| Pcs/Carton | 18 |
| Barcode | 5291889058922 |
| HS Code | 9405413990 |

## Certification & Warranty

| | |
|---|---|
| Warranty | 2 years |