20 Industrial & Floodlights>The IP65 CCT V & PV Range Enclosed

38140N/V



36W CCT and Power variable linear fitting for surface installation.

Complete with power variable driver

Complies with standard EN60598-1 and any other specific standards.

IP65 IK08 CCT V PV 80 CRI CE

Downloads

IES

Dimensions



Physical Specification

Item Group	20 Industrial & Floodlights
Family	The IP65 CCT V & PV Range Enclosed
Order Code	38140N/V
Colour	Grey
Material	PC
Diffuser Material	PC
Shape	Rectangular
Length	1200mm
Width	70mm
Height	60mm
Surface Ceiling	Yes
Surface Wall	Yes

Suspended Ceiling	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No
IK Rating	8

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	20W-25W-30W-36W
IP Rating	IP65
Light Source	LED built in
F Mark	

Fitting

Light Source	LED built in
LED Type	SMD

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Dimmable	No
Protection	0

Illumination Data

Colour Temperature	3000K-4000K-6500K
Lumen Output	4320lm (36W)
Light Efficiency	120lm/W
CRI	80
Beam Angle	120
Illumination Diagram	

Packing Info

Box Weight	1.212kg
Pcs/Carton	16
Barcode	5291889083627
HS Code	9405114090

Certification & Warranty

Warranty	3 years