10 Office & Kitchen>CCT V LED Linear Profiles Medium Size

# 38150A/B/V



CCT and Power variable 40W UGR19 Linear system with diffuser for surface or suspended installation, ideal for offices.

Complete with power variable driver

Complies with standard EN60598-1 and any other specific standards.

IP20 CCT V PV 90 CRI UGR19 CE

## Downloads

IES

## Dimensions





## Gallery



## Accessories


050170


050170C/B

## Related items



050170D/B/V



38150E/B

## Physical Specification

| | |
|---|---|
| Item Group | 10 Office & Kitchen |
| Family | CCT V LED Linear Profiles Medium Size |
| Order Code | 38150A/B/V |
| Colour | Black |
| Material | Aluminium |
| Shape | Rectangular |
| Length | 1200mm |
| Width | 35mm |
| Height | 70mm |
| Surface Ceiling | Yes |
| Suspended Ceiling | Yes |
| Indoor | Yes |
| Adjustable | No |

## Electrical Characteristics

| | |
|---|---|
| Gear | Built In |

### Fitting + Driver

| | |
|---|---|
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class | |
| Power(Watts) | 20W-30W-40W |
| IP Rating | IP20 |

| | |
|---|---|
| Light Source | LED built in |
| Dimmable | No |
| Cable Length | 300cm |
| F Mark |  |

### Fitting

| | |
|---|---|
| Input Type | Constant Current |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | SMD |

### Gear

| | |
|---|---|
| Gear Type | Led Driver |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| IP Rating | IP20 |
| Dimmable | No |
| Protection | 0 |

## Illumination Data

| | |
|---|---|
| Colour Temperature | 3000K-4000K-5000K |
| Lumen Output | 3400lm (40W) |
| Light Efficiency | 85lm/W |
| CRI | 90 |
| Illumination Diagram |  |
| UGR | 19 |

## Packing Info

| | |
|---|---|
| Box Weight | 1.992kg |

| | |
|---|---|
| Pcs/Carton | 12 |
| Barcode | 5291889082248 |
| HS Code | 9405413990 |

## Certification & Warranty

| | |
|---|---|
| Warranty | 3 years |