10 Office & Kitchen>CCT V LED Linear Profiles Medium Size

38151A/B/V



CCT and Power variable 50W UGR19 Linear system with diffuser for surface or suspended installation, ideal for offices.

Complete with power variable driver.

Complies with standard EN60598-1 and any other specific standards.

IP20 CCT V PV 90 CRI UGR19 CE

Downloads

IES

Dimensions




Gallery




Accessories


050170


050170C/B

Related items



050170D/B/V



38150E/B

Physical Specification

Item Group	10 Office & Kitchen
Family	CCT V LED Linear Profiles Medium Size
Order Code	38151A/B/V
Colour	Black
Material	Aluminium
Shape	Rectangular
Length	1500mm
Width	70mm
Height	35mm
Surface Ceiling	Yes
Suspended Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	30W-40W-50W
IP Rating	IP20

Light Source	LED built in
Dimmable	No
Cable Length	300cm
F Mark	

Fitting

Input Type	Constant Current
IP Rating	IP20
Light Source	LED built in
LED Type	SMD

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
IP Rating	IP20
Dimmable	No
Protection	0

Illumination Data

Colour Temperature	3000K-4000K-5000K
Lumen Output	4250lm (50W)
Light Efficiency	85lm/W
CRI	90
Illumination Diagram	
UGR	19

Packing Info

Box Weight	2.466kg

Pcs/Carton	9
Barcode	5291889082569
HS Code	9405413990

Certification & Warranty

Warranty	3 years