10 Office & Kitchen>CCT V Opal Recessed LED Linear Profiles

38152R/W/V



CCT and Power variable 40W recessed linear fitting with diffuser, ideal for offices.

Complete with power variable driver.

Complies with standard EN60598-1 and any other specific standards.

IP20 CCT V PV 90 CRI CE


Downloads


IES

Dimensions




Gallery





Related items



38152RC/W/V

Physical Specification

Item Group	10 Office & Kitchen
Family	CCT V Opal Recessed LED Linear Profiles

Order Code	38152R/W/V
Colour	White
Material	Aluminium
Shape	Rectangular
Length	1210mm
Width	70mm
Height	60mm
Cutout Hole Width	60mm
Cutout Hole Length	1200mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⏚
Power(Watts)	20W-30W-40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
IP Rating	IP20

Light Source	LED built in
LED Type	SMD

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
IP Rating	IP20
Dimmable	No

Illumination Data

Colour Temperature	3000K-4000K-5000K
Lumen Output	3600lm (40W)
Light Efficiency	90lm/W
CRI	90
Beam Angle	120°
Illumination Diagram	

Packing Info

Box Weight	2.366kg
Pcs/Carton	12
Barcode	5291889082576
HS Code	9405413990

Certification & Warranty

Warranty	3 years