05 Downlights Fixed>Floating Square Panels Range Adjustable Cut Out Hole 50114CE/C



14W Downlight LED, IP20.

Complete with 300mA driver.

Complies with standard EN60598-1 and any other specific standards.

IP20 90 CRI CE

Downloads

IES

Dimensions



Gallery



Physical Specification

Item Group	05 Downlights Fixed
Family	Floating Square Panels Range Adjustable Cut Out Hole
Order Code	50114CE/C
Colour	White
Material	Aluminium
Diffuser Material	PC
Shape	Rectangular

Length	160mm
Width	160mm
Height	10mm
Cutout Hole Diameter	70mm-140mm
Recessed Ceiling	Yes
Depth Required	50mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⧈
Power(Watts)	14W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	300mA
Voltage	36,5V
Safety Class	III
Power(Watts)	10,95W
IP Rating	IP20
Light Source	LED built in

LED Type	SMD 4014
LED Brand	Zhaochi

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	7,2-12,6W
Power Factor	0,85
Constant Current	Yes
300mA	24-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Eaglerise

Illumination Data


Colour Temperature	4000K
Lumen Output	1610lm
Light Efficiency	115lm/W
CRI	90
Illumination Diagram	

Packing Info

Box Weight	0.332kg
Pcs/Carton	40
Barcode	5291889073956

HS Code	9405413990

Energy Label



Energy Class	D
Energy Consumption	14kWh/1000h

Certification & Warranty

Warranty	2 years