05 Downlights Fixed>UGR19 CCT V Office Range Square

50130UV/W/V



30W SMD LED UGR19 downlight with adjustable CCT, IP44.

Complete with 750mA driver.


Complies with standard EN60598-1 and any other specific standards.

IP44 90 CRI UGR19 CE


Downloads

IES

Dimensions



Gallery



Physical Specification

Item Group	05 Downlights Fixed
Family	UGR19 CCT V Office Range Square
Order Code	50130UV/W/V
Colour	White
Material	Die Cast
Shape	Rectangular
Length	225mm

Width	225mm
Height	50mm
Cutout Hole Width	205mm
Cutout Hole Length	205mm
Recessed Ceiling	Yes
Depth Required	80mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⧈
Power(Watts)	30W
IP Rating	IP44
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	750mA
Voltage	38V
Safety Class	III
Power(Watts)	28,5W
IP Rating	IP44
Light Source	LED built in

LED Type	SMD 2835
LED Brand	Epistar
F Mark	

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	24,75-30W
Power Factor	0,9
Constant Current	Yes
750mA	33-40V
IP Rating	IP44
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud
Protection	Short Circuit and Overload

Illumination Data

Colour Temperature	3000K-4000K-6000K
Lumen Output	3300lm
Light Efficiency	110lm/W
CRI	90
Illumination Diagram	
UGR	19

Packing Info

Box Weight	1.180kg
Pcs/Carton	10
Barcode	5291889075202
HS Code	9405413990

Certification & Warranty

Warranty	3 years