05 Downlights Fixed>Panels 600x600mm

50140BU/W/V



40W 60x60 adjustable CCT recessed backlit LED panel with microprismatic diffuser for T-rail false ceilings.

Uniform lighting, ideal for commercial applications.

Complete with 1000mA driver.


Complies with standard EN60598-1 and any other specific standards.

IP20 80 CRI UGR19

Downloads

IES

Dimensions



Related items


050017


050108


89044L

Physical Specification

Item Group	05 Downlights Fixed
Family	Panels 600x600mm
Order Code	50140BU/W/V
Colour	White
Material	Aluminium + Steel
Shape	Rectangular
Length	595mm

Width	595mm
Height	30mm
Recessed T-Ceiling	Yes
Depth Required	60mm
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⧈
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	1000mA
Voltage	38V
Safety Class	III
Power(Watts)	38W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835

LED Brand	Sanan

Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	33-40W
Power Factor	0,9
Constant Current	Yes
1000mA	33-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic

Illumination Data

Colour Temperature	3000K-4000K-5700K
Lumen Output	3600lm-4000lm-3800lm
Light Efficiency	90lm/W - 100lm/W - 95Lm/W
CRI	80
Illumination Diagram	
UGR	19

Packing Info

Box Weight	2.250kg
Pcs/Carton	4
Barcode	5291889077145
HS Code	9405119090

Certification & Warranty

Warranty	3 years