06 Downlights Fixed LED>Surface/Recessed Panels

62116FA/W/W



16W Downlight LED, IP20

Complete with 230mA driver.


Complies with standard EN60598-1 and any other specific standards.

IP20 80 CRI CE

Downloads

IES

Dimensions



Physical Specification

Item Group	06 Downlights Fixed LED
Family	Surface/Recessed Panels
Order Code	62116FA/W/W
Colour	White
Material	Plastic
Shape	Rectangular
Length	235mm
Width	235mm
Height	17mm
Cutout Hole Diameter	70mm-190mm
Recessed Ceiling	Yes
Depth Required	50mm

Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	16W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	230mA
Voltage	68V
Power(Watts)	15,6W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar

Gear

Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes

60 Hz	Yes
Power(Watts)	16W
Power Factor	0,5
Constant Current	Yes
Output	230mA
IP Rating	IP20
Safety Class	
Dimmable	No
Output Terminal	Cable

Illumination Data

Colour Temperature	3000K
Lumen Output	1500lm
Light Efficiency	93,75lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	0.665kg
Pcs/Carton	20
Barcode	5291889067788

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes