13 Plafo>The Floating Plafo Aluminium

62140FB/W/W



40W LED slim plafo light, IP20, suitable for residential and commercial application.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Physical Specification

Item Group	13 Plafo
Family	The Floating Plafo Aluminium
Order Code	62140FB/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	43mm
Diameter	395mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	External-Included

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⏚
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	1000mA
Voltage	39V
Safety Class	III
Power(Watts)	39W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Sanan
F Mark	F

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes

Power(Watts)	25-42W
Power Factor	0,9
Constant Current	Yes
1000mA	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	40°C
Operating Temp	80°C
Housing Material	Plastic
Output Terminal	Cable
Fast Connector	Yes
Fast Connector Type	Other
Brand	Lifud

Illumination Data

Colour Temperature	3000K
Lumen Output	3500lm
Light Efficiency	87,5lm/W
CRI	90
Illumination Diagram	

Packing Info

Box Weight	2.050kg
Pcs/Carton	4
Barcode	5291889057406
HS Code	9405413990

Certification & Warranty

Warranty	3 years