20 Industrial & Floodlights>The Industrial IP65 Linear Range Adjustable

63150L/C



150W SMD LED Linear Industrial High Bay.

Complete with non-dimmable driver.

Complies with standard EN60598-1 and any other specific standards.

IP65 IK06 80 CRI ADJUSTABLE CE

Downloads

IES

Dimensions



Physical Specification

Item Group	20 Industrial & Floodlights
Family	The Industrial IP65 Linear Range Adjustable
Order Code	63150L/C
Colour	Black
Material	Aluminium
Shape	Rectangular
Length	670mm
Width	80mm
Height	95mm
Surface Ceiling	Yes
Surface Wall	Yes
Indoor	Yes

Outdoor	Yes
Adjustable	1 Direction
IK Rating	6

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	120-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⏚
Power(Watts)	150W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
Cable Length	100cm
F Mark	F

Fitting

Input Type	Constant Current
Light Source	LED built in
LED Type	SMD

Gear

Gear Type	Led Driver
Input Voltage	120-240V
Safety Class	⏚

Illumination Data

Colour Temperature	4000K
Lumen Output	15000lm
Light Efficiency	100lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	

Packing Info

Box Weight	1.980kg
Pcs/Carton	4
Barcode	5291889088752
HS Code	9405413990

Certification & Warranty

Warranty	3 years