08 Track Lights>The COB Track Light Range Aluminium

# 65611NT/B/C



15W track spot with COB LED, ideal for shops and showrooms.

Complete with driver.


Complies with standard EN60598-1 and any other specific standards.

IP20 80 CRI ADJUSTABLE CE

## Downloads

IES

## Dimensions




## Related items


40001A/B


40002A/B


40003A/B


40003R/B

## Physical Specification

| | |
|---|---|
| Item Group | 08 Track Lights |
| Family | The COB Track Light Range Aluminium |
| Order Code | 65611NT/B/C |
| Colour | Black |
| Material | Aluminium |
| Shape | Circular |
| Height | 110mm |

| | |
|---|---|
| Diameter | 80mm |
| Track mounted | Yes |
| Indoor | Yes |
| Adjustable | 2 Directions |

## Electrical Characteristics

| | |
|---|---|
| Gear | Built In |

### Fitting + Driver

| | |
|---|---|
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class | ⏚ |
| Power(Watts) | 15W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |

### Fitting

| | |
|---|---|
| Input Type | Constant Current |
| Input Current | 400mA |
| Voltage | 36V |
| Safety Class | III |
| Power(Watts) | 14,4W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | COB |
| LED Brand | Sanan |

### Gear

| | |
|---|---|
| Gear Type | Led Driver |

| | |
|---|---|
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 10-16W |
| Power Factor | 0,9 |
| Constant Current | Yes |
| 400mA | 25-40V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Housing Material | Plastic |
| Output Terminal | Connector |
| Brand | Lifud |
| Protection | Short Circuit Protection |

## Illumination Data

| | |
|---|---|
| Colour Temperature | 4000K |
| Lumen Output | 1300lm |
| Light Efficiency | 86,67lm/W |
| CRI | 80 |
| Beam Angle | 38° |
| Illumination Diagram |  |

## Packing Info

| | |
|---|---|
| Box Length | 25cm |
| Box Width | 13cm |
| Box Height | 10cm |
| Box Weight | 0.850kg |
| Pcs/Carton | 10 |
| Barcode | 5291889057840 |

| | |
|---|---|
| HS Code | 9405413990 |

## Certification & Warranty

| | |
|---|---|
| Warranty | 3 years |