19 Garden & Underwater>LED Bollard Lights Aluminium

67034/AN/W



15W LED Bollard, IP54 for Garden illumination.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.

IP54 IK05 80 CRI CE

Downloads

IES

Dimensions



Physical Specification

Item Group	19 Garden & Underwater
Family	LED Bollard Lights Aluminium
Order Code	67034/AN/W
Colour	Anthracite
Material	Die Cast
Diffuser Material	PC
Shape	Circular
Height	850mm
Diameter	120mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No

IK Rating	5

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⏚
Power(Watts)	15W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	350mA
Voltage	40V
Power(Watts)	14W
IP Rating	IP54
Light Source	LED built in
LED Brand	Cree

Gear

Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	13-15W

Power Factor	0,9
Constant Current	Yes
350mA	37-43V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20~55°C
Housing Material	Plastic
Output Terminal	Connector
Brand	HEP
Protection	Short Circuit

Illumination Data

Colour Temperature	3000K
Lumen Output	450lm
Light Efficiency	30lm/W
CRI	80
Beam Angle	50°
Illumination Diagram	

Packing Info

Box Length	88,5cm
Box Width	14,5cm
Box Height	14,5cm
Box Weight	4.200kg
Pcs/Carton	4
Barcode	5291889051176
HS Code	9405413990

Certification & Warranty

Warranty	2 years
Weee Directive	Yes