13 Plafo>The LED Plafo Outdoor

# 67280N/AN/W



16W LED plafo light, IP65, ideal for both indoor and outdoor installation.

Supplied with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.

IP65 IK08 80 CRI

## Downloads

IES

## Dimensions




## Physical Specification

| | |
|---|---|
| Item Group | 13 Plafo |
| Family | The LED Plafo Outdoor |
| Order Code | 67280N/AN/W |
| Colour | Anthracite |
| Material | Plastic |
| Diffuser Material | PC |
| Shape | Circular |
| Height | 75mm |
| Diameter | 260mm |
| Surface Ceiling | Yes |
| Indoor | Yes |
| Outdoor | Yes |

| | |
|---|---|
| Adjustable | No |
| IK Rating | 8 |

## Electrical Characteristics

| | |
|---|---|
| Gear | Built In |

### Fitting + Driver

| | |
|---|---|
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class | ⧈ |
| Power(Watts) | 16W |
| IP Rating | IP65 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark | ▽F |

### Fitting

| | |
|---|---|
| Input Type | Constant Current |
| Input Current | 500mA |
| Voltage | 30V |
| Power(Watts) | 15W |
| IP Rating | IP65 |
| Light Source | LED built in |
| LED Type | SMD 2835 |
| LED Brand | Epistar |
| LED Number | 81 |
| F Mark | ▽F |

### Gear

| | |
|---|---|
| Gear Type | Led Driver |

| | |
|---|---|
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 8,5-16W |
| Power Factor | 0,9 |
| Constant Current | Yes |
| 500mA | 19-32V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Housing Material | Plastic |
| Output Terminal | Connector |
| Brand | Eaglerise |

## Illumination Data

| | |
|---|---|
| Colour Temperature | 3000K |
| Lumen Output | 960lm |
| Light Efficiency | 60lm/W |
| CRI | 80 |
| Illumination Diagram |  |

## Packing Info

| | |
|---|---|
| Box Length | 27cm |
| Box Width | 27cm |
| Box Height | 8cm |
| Box Weight | 0.980kg |
| Pcs/Carton | 10 |
| Barcode | 5291889043287 |
| HS Code | 9405114090 |

## Certification & Warranty

| | |
|---|---|
| Warranty | 2 years |