13 Plafo>Outdoor Slim LED Plafo Aluminium

67363A/AN/W



30W LED slim plafo, IP54, ideal for both indoor and outdoor installation.

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.

IP54 80 CRI CE

Downloads

IES CE

Dimensions



Physical Specification

Item Group	13 Plafo
Family	Outdoor Slim LED Plafo Aluminium
Order Code	67363A/AN/W
Colour	Anthracite
Material	Die Cast
Shape	Rectangular
Length	300mm
Width	300mm
Height	49mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes

Adjustable	No

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⏚
Power(Watts)	30W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	700mA
Voltage	40V
Power(Watts)	28W
IP Rating	IP54
Light Source	LED built in
LED Type	SMD 3014
LED Brand	Edison
LED Number	299
F Mark	F

Gear

Gear Type	Led Driver
Input Voltage	220-240V

50 Hz	Yes
60 Hz	Yes
Power(Watts)	20-30W
Power Factor	0,9
Constant Current	Yes
700mA	28-43V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Eaglerise

Illumination Data

Colour Temperature	3000K
Lumen Output	2500lm
Light Efficiency	83,33lm/W
CRI	80
Beam Angle	120°
Illumination Diagram	

Packing Info

Box Length	25,5cm
Box Width	25,5cm
Box Height	6,5cm
Box Weight	1.733kg
Pcs/Carton	6
Barcode	5291889040804
HS Code	9405413990

Certification & Warranty

Warranty	2 years