13 Wall & Ceiling LED>Outdoor Slim Range Up & down beam

67376A/AN/W



2x6W, IP54,SMD 2835, Outdoor Slim Range Up & down beam.

Complies with standard EN60598-1 and any other specific standards.

IP54 80 CRI CE

Downloads

Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	Outdoor Slim Range Up & down beam
Order Code	67376A/AN/W
Colour	Anthracite
Material	Die Cast
Shape	Rectangular
Length	175mm
Width	90mm
Height	28mm
Surface Wall	Yes
Indoor	Yes
Outdoor	Yes

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	2x6W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	350mA
Voltage	16V
Power(Watts)	5,6W
IP Rating	IP54
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Edison

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	2,9-6,1W
Power Factor	0,5

Constant Current	Yes
350mA	8,5-17,5V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	50ºC
Operating Temp	75ºC
Housing Material	Plastic
Output Terminal	Cable
Brand	Eaglerise

Illumination Data

Colour Temperature	3000K
Lumen Output	2x420lm
Light Efficiency	70lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	0.625kg
Pcs/Carton	12
Barcode	5291889043652
HS Code	9405409900

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes