19 Garden & Underwater>The LED Bollards Range Cone reflector

67410/AN/C



12W LED Bollard, IP65 for Garden illumination.

Complete with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.

IP65 IK08 80 CRI CE

Downloads

IES

Dimensions



Physical Specification

Item Group	19 Garden & Underwater
Family	The LED Bollards Range Cone reflector
Order Code	67410/AN/C
Colour	Anthracite
Material	Die Cast
Diffuser Material	PC
Shape	Circular
Height	800mm
Diameter	120mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No

IK Rating	8

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	⏚
Power(Watts)	12W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	500mA
Voltage	22V
Power(Watts)	11W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Osram

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes

Power(Watts)	7,25-12W
Power Factor	0,9
Constant Current	Yes
500mA	14,5-24V
IP Rating	IP20
Safety Class	
Dimmable	No
Ambient Temp	-20~55°C
Operating Temp	85°C
Housing Material	Plastic
Output Terminal	Connector
Brand	Eaglerise
Protection	Short Circuit

Illumination Data

Colour Temperature	4000K
Lumen Output	1000lm
Light Efficiency	83,33lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	3.550kg
Pcs/Carton	2
Barcode	5291889051640
HS Code	9405413990

Certification & Warranty

Warranty	2 years
Weee Directive	Yes