13 Wall & Ceiling LED>Outdoor Wall Lights

67492P/AN/W



12W LED Wall light with movement sensor.

Working time-delay: 5s, 30s, 1Min,3 Min,5 Min, 8 Min.
Ambient light : Distance: 8m

Complete with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.

IP54 80 CRI CE

Downloads

IES

Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	Outdoor Wall Lights
Order Code	67492P/AN/W
Colour	Anthracite
Material	Plastic
Diffuser Material	PC
Shape	Rectangular
Length	170mm
Width	140mm
Height	170mm
Surface Wall	Yes
Indoor	Yes

Outdoor	Yes

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	12W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	

Fitting

Input Type	Constant Current
Input Current	300mA
Voltage	38V
Power(Watts)	11,6W
IP Rating	IP54
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes

Power(Watts)	6-12W
Power Factor	0,5
Constant Current	Yes
300mA	20-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Eaglerise

Illumination Data

Colour Temperature	3000K
Lumen Output	600lm
Light Efficiency	50lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	0.875kg
Pcs/Carton	12
Barcode	5291889066187
HS Code	9405114090

Certification & Warranty

Warranty	2 Years
Weee Directive	Yes