19 Garden & Underwater>Corridor Bollards

# 67494A/AN/W



3W Bollard with 2x1000W Schuko Sockets , IP44.

Complete with 350mA driver


Complies with standard EN60598-1 and any other specific standards.

IP44 IK05 80 CRI CE

## Downloads

IES

## Dimensions




## Physical Specification

| | |
|---|---|
| Item Group | 19 Garden & Underwater |
| Family | Corridor Bollards |
| Order Code | 67494A/AN/W |
| Colour | Anthracite |
| Material | Die Cast |
| Shape | Circular |
| Height | 490mm |
| Diameter | 100mm |
| Surface Floor/Ground | Yes |
| Outdoor | Yes |
| Adjustable | No |
| IK Rating | 5 |

## Electrical Characteristics

| | |
|---|---|
| Gear | Built In |

### Fitting + Driver

| | |
|---|---|
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class |  |
| Power(Watts) | 3W |
| IP Rating | IP44 |
| Light Source | LED built in |
| Dimmable | No |
| F Mark |  |

### Fitting

| | |
|---|---|
| Input Type | Constant Current |
| Input Current | 350mA |
| Voltage | 8V |
| Power(Watts) | 2,8W |
| IP Rating | IP44 |
| Light Source | LED built in |
| LED Type | SMD 3014 |
| LED Brand | Philips |

### Gear

| | |
|---|---|
| Gear Type | Led Driver |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 2,1-4,2W |
| Power Factor | 0,9 |

| | |
|---|---|
| Constant Current | Yes |
| 350mA | 6-12V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Housing Material | Plastic |
| Brand | KGP |

## Illumination Data

| | |
|---|---|
| Colour Temperature | 3000K |
| Lumen Output | 240lm |
| Light Efficiency | 80lm/W |
| CRI | 80 |
| Illumination Diagram |  |

## Packing Info

| | |
|---|---|
| Box Weight | 2.075kg |
| Pcs/Carton | 4 |
| Barcode | 5291889067092 |
| HS Code | 9405413990 |

## Certification & Warranty

| | |
|---|---|
| Warranty | 2 years |