21 Industrial & Floodlights>The LED Park Light Die cast

70112/B/C



LED outdoor light for poles 3m and higher. Ideal for parks, parkings, playgrounds.Post Diamerter 60mm.

Complete with 2400mA driver.


Complies with standard EN60598-1 and any other specific standards.

IP66 IK08 80 CRI CE


Downloads

IES

Dimensions



Gallery



Physical Specification

Item Group	21 Industrial & Floodlights
Family	The LED Park Light Die cast
Order Code	70112/B/C
Colour	Black
Material	Die Cast
Shape	Circular
Height	530mm

Diameter	450mm
Surface Floor/Ground	Yes
Outdoor	Yes
Adjustable	No
IK Rating	8

Electrical Characteristics

Gear	Built In

Fitting + Driver

Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	75W
IP Rating	IP66
Light Source	LED built in
Dimmable	No
Cable Length	150cm
F Mark	

Fitting

Input Type	Constant Current
Input Current	2400mA
Voltage	30V
Power(Watts)	72W
IP Rating	IP66
Light Source	LED built in
LED Brand	Seoul

Gear

Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Constant Current	Yes
Output	1730mA
Voltage Range	25-56V
IP Rating	IP20
Safety Class	
Dimmable	No

Illumination Data

Colour Temperature	4000K
Lumen Output	9000lm
Light Efficiency	120lm/W
CRI	80
Illumination Diagram	

Packing Info

Box Weight	9.300kg
Pcs/Carton	1
Barcode	5291889068327
HS Code	9405413990

Certification & Warranty

Warranty	5 years
Weee Directive	Yes