




## KALU

wall and ceiling light, three-headed, LED, 3000K, white/black, 60°

As one would expect, the LED extension of the popular KALU series guarantees the utterly free adjustment of lamp heads. Fitted with dimmable, high output LEDs, the KALU series has just become even more efficient and versatile! Available in matt black or black and white, KALU wall and ceiling light is supplied ready for direct connection to 230V mains supply.



## TECHNICAL DATA

Item no.	1000132
Number of different light outlets	3
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	Leading edge,trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	1050 mA
Safety class	I
Wattage	47 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Rated standby power	0.5 W
Number of luminaires at LS B16A	28
Number of luminaires at LS C16A	28
Stroboscopic effect (SVM)	0.03
Lumen	3000 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white

Light Source

916610	
--------	---

CRI	80
LXXBXX data	L80B50
Service life	40000 h
Risk Group	1
Length	43 cm
Width	8.9 cm
Height	16 cm
Net weight	2.25 kg
Gross weight	2.671 kg
BIG WHITE Page	403