




## KALU

wall and ceiling light, four-headed, LED, 3000K, square, white/black, 60°


As one would expect, the LED extension of the popular KALU series guarantees the utterly free adjustment of lamp heads. Fitted with dimmable, high output LEDs, the KALU series has just become even more efficient and versatile! Available in matt black or black and white, KALU wall and ceiling light is supplied ready for direct connection to 230V mains supply.



## TECHNICAL DATA

Item no.	1000136
Number of different light outlets	4
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling,Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	60 W
Rated standby power	0.5 W
Stroboscopic effect (SVM)	0.03
Lumen	4000 lm
Colour temperature	3000 Kelvin
Beam angle	60 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	40000 h
Light distribution	rotational symmetric

Light Source

916610		Light outlet	direct
		Length	28 cm
		Width	29 cm
		Height	16 cm
		Net weight	3.721 kg
		Gross weight	4.382 kg
		BIG WHITE Page	403