




SHELL 15

WL, LED Indoor surface-mounted wall light, 3000K, white

The elegant SHELL wall light is a combination of aluminium and acrylic glass. The dimmable wall light is available in two sizes. The one or two long-life LEDs each have output of 12W, and provide the required luminous intensity. The wall light has a strong design and can be directly connected to the 230V mains supply as it has an integrated LED driver.



TECHNICAL DATA

Item no.	1000422
Number of different light outlets	1
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	I
Wattage	15 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	5 A
Duration of inrush current	100 µs
Stroboscopic effect (SVM)	0.01
Lumen	1400 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	white

Light Source

780780	
--------	---

CRI	80
LXXBXX data	L70B50
Service life	50000 h
Risk Group	1
Width	12.6 cm
Height	7 cm
Depth	16 cm
Net weight	0.933 kg
Gross weight	1.135 kg
BIG WHITE Page	365