




## SHELL 30

WL, LED Indoor surface-mounted wall light, 3000K, white

The elegant SHELL wall light is a combination of aluminium and acrylic glass. The dimmable wall light is available in two sizes. The one or two long-life LEDs each have output of 12W, and provide the required luminous intensity. The wall light has a strong design and can be directly connected to the 230V mains supply as it has an integrated LED driver.



## TECHNICAL DATA

Item no.	1000423
Number of different light outlets	1
IP Code	IP 20
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	700 mA
Safety class	I
Wattage	54 W
Level of inrush current	20 A
Stroboscopic effect (SVM)	0.01
Lumen	5600 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	white
CRI	80
LXXBXX data	L70B50
Service life	50000 h

Light Source

780780	
--------	---

Light distribution	symmetric
Light outlet	direct
Light outlet 2	indirect
Risk Group	1
Width	28.6 cm
Height	7 cm
Depth	16 cm
Net weight	1.802 kg
Gross weight	2.069 kg
BIG WHITE Page	365